

Power **GLIDE**



Easy-to-use, angle-adjustable hand control lever



Levers for easy removal



Dual-wheel design for added traction and stability



POWER UP YOUR MANUAL WHEELCHAIR

The new Power Glide makes it easier to push a manual wheelchair. The Power Glide attaches directly to manual wheelchairs and assists caregivers with operation. The Power Glide has a dual-wheel design, a maximum speed of up to 5.5 km/h (3.4 mph), a range of up to 16 km (10 miles), and a weight capacity of 136 kg (300 lbs.). Standard features include a travel bag and extended push handles for added convenience. A direct drive system provides traction on loose gravel and wet grass, allowing manual chairs to go just about anywhere.

SPECIFICATIONS

Maximum speed¹:	Up to 5.5 km/h (3.4 mph)
Range per charge¹:	Up to 16 km (10 miles)
Turning radius:	85 cm (33.8")
Motor:	DC12V, 75W or 280W
Battery:	12V, 18AH
Charger:	1.5 A, off-board
Drive wheel:	20.23 cm (8") solid
Weight capacity:	136 kg (300 lbs.)
Dimensions²:	Length: 30 cm (11.81") Width: 20 cm (7.87") Height: 24.5 cm (9.65")
Base weight:	7.7 kg (17 lbs.)
Battery weight³:	6.8 kg (15 lbs.)
Total weight:	14 kg (31 lbs.)
Fits wheelchair widths:	35.5 cm - 50.8 cm (14" - 20")

¹ Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure.

² Due to manufacturing tolerances and continued product improvement, this specification is subject to a variance of +/- 3%.

³ Battery weight may vary based on manufacturer.



FEATURES

- Dual-wheel design for added traction and stability
- 136 kg (300 lbs.) weight capacity
- Direct drive system provides traction on loose gravel and wet grass
- Maximum speed up to 5.5 km/h (3.4 mph)
- Range up to 16 km/h (10 miles)
- Travel bag included
- Extended push handles included

The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.